NSN 4810-01-158-1505

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-158-1505 **Thread Direction:** Right-hand all ends Offset Distance: 1.260 inches Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Universal **Maximum Operating Temp:** 165.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 1.900 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.500 inches all ends **Voltage In Volts And Current Type:** 110.0 ac Phase: Single Frequency In Hertz: 50.0 Material: Steel comp 303 **Material Specification:** Mil-s-7720 military specification single material response Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends

Shelf Life:

N/a

NSN 4810-01-158-1505

Solenoid Valve - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-7720 spec.