NSN 4810-01-168-8684



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-168-8684 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) 2nd end **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe 2nd end **Mounting Position:** Vertical **Maximum Operating Pressure:** 50.0 pounds per square inch single response **Thread Size:** 0.375 inches 1st end Seat Angle: 37.0 degrees 1st end **Voltage In Volts And Current Type:** 28.0 dc **Special Features:** Outlet exhaust parallel to intake Material: Aluminum alloy Media For Which Designed: Air single response **Special Test Features:** Selected item drawing **Style Designator:** Err-090 **Test Data Document:** 97942-585r559 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Unif 1st end Shelf Life:

Thread Series Designator:

N/a

NSN 4810-01-168-8684

Solenoid Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A046b0