NSN 4810-01-194-6795

Solenoid Valve - Page 1 of 2

Thread Class: 3a all ends

Thread Direction: Right-hand all ends



View Online at https://aerobasegroup.com/nsn/4810-01-194-6795

Flow Control Device:
Disk
Flow Control Device Normal Operation Position
Universal
Maximum Operating Temp:
167.0 degrees fahrenheit single response
Connection Style:
G42 flared (tube) all ends
Current Rating In Amps:
1.000
Valve Operation Method:
Solenoid
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
20 all ends
Maximum Operating Pressure:
40.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees all ends
Voltage In Volts And Current Type:
24.0 dc and 30.0 dc
Special Features:
150 micron screens both ports
Material:
Stainless steel body
Media For Which Designed:
Oxygen, gaseous 2nd response
Style Designator:
Err-090
Thread Series Designator:
Unj all ends
Shelf Life:
N/a

NSN 4810-01-194-6795

Solenoid Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0