

View Online at <https://aerobasegroup.com/nsn/4810-01-206-7053>

**Body Material:**

Aluminum

**Mounting Provision:**

Threaded mounting holes

**Temperature Rating:**

225.0 degrees fahrenheit

**Bore Diameter:**

6.940 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.500 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.750 inches

**Longest Vertical Distance Between Mounting Centers:**

1.750 inches

**End Application:**

Model mpd-16-f152/poco-boh6 lube oil manifold

**Mounting Facility Thread Class:**

2b

**Mounting Facility Thread Direction:**

Right-hand

**Shaft Rotation Direction:**

Clockwise and counterclockwise

**Output Drive Torque Rating:**

2200.0 inch-pounds

**Mounting Provision Arrangement Style:**

Three hole triangular

**Pressure Rating:**

120.0 pounds per square inch

**Rotation In Deg:**

110.0

**Mounting Facility Thread Series Designator:**

Unc

**Mounting Facility Thread Diameter:**

0.375 inches

**Mounting Facility Thread Qty Per Inch (tpi):**

16

**Design Characteristics:**

Double acting single cylinder

**Mounting Facility Thread Length:**

0.500 inches

**Port Location And Quantity:**

2 center section

**Port Style:**

Gasket seal

**Port Thread Series Designator:**

Npt

**Port Pipe Thread Size:**

0.250 inches

**Special Features:**

Vane operated completely sealed and weatherproofed actuator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A34200