NSN 4810-01-211-7013

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-211-7013 Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Bolt Hole Quantity:** 6 all ends **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Current Rating In Amps:** 0.100 **Valve Operation Method:** Solenoid Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Horizontal Valve Size: 1.500 inches **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Voltage In Volts And Current Type:** 115.0 ac **Outside Diameter:** 5.062 inches all ends **Face To Face Distance:** 9.625 inches Thickness: 0.438 inches all ends **Bolt Hole Diameter:** 0.562 inches all ends **Bolt Circle Diameter:** 8.938 inches all ends Flange Face Design: Plain all ends Phase: Single Frequency In Hertz:

60.0 Material:

Copper alloy body

NSN 4810-01-211-7013

Solenoid Valve - Page 2 of 2



Style	Des	ian	ato	r:
,				

A1a straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0