## NSN 4810-01-212-6802



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-212-6802 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.125 inches Flow Control Device: Stem Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.800 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 130.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single **Special Features:** Explosion proof and watertight solenoid enclosure Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device Media For Which Designed: Gas, inert 3rd response **Style Designator:** A1 straight thru **Thread Series Designator:** 

Npt all ends Shelf Life:

N/a

## NSN 4810-01-212-6802

Solenoid Valve - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0