NSN 4810-01-213-7968

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-213-7968 **Thread Direction:** Right-hand all ends Flow Control Device: Piston Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 353.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.047 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Inlet/outlet Operating Pressure Differential:** 1.0 pounds per square inch **Maximum Operating Pressure:** 125.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single **Special Features:** Furnished w/instruction sheet Frequency In Hertz: 60.0 Material: Stainless steel seat Media For Which Designed: Water-oil-gas single response **Style Designator:** A8 straight through y-pattern **Thread Series Designator:** Npt all ends Shelf Life:

N/a

NSN 4810-01-213-7968

Solenoid Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A046b0