# NSN 4810-01-218-3306

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-218-3306

# Thread Direction:

Right-hand all ends

## Offset Distance:

1.125 inches

# Flow Control Device:

Poppet

## Flow Control Device Normal Operation Position:

Closed

### Connection Style:

G9 plain, optional en (pipe) all ends

# Current Rating In Amps:

0.500

### Valve Operation Method:

Solenoid

#### **Connection Type:**

Threaded internal pipe all ends

### **Mounting Position:**

Horizontal or vertical

# Maximum Operating Pressure:

3000.0 pounds per square inch single response

# Thread Size:

0.750 inches all ends

#### Voltage In Volts And Current Type:

110.0 ac

# Phase:

Single

# Frequency In Hertz:

60.0

#### Material:

Steel flow control device

#### Media For Which Designed:

Hydraulic fluid, mineral base single response

#### Style Designator:

A6 straight through w/offset

#### **Thread Series Designator:**

Nptf all ends

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 4810-01-218-3306

Solenoid Valve - Page 2 of 2

**Fiig:** A046b0

