## NSN 4810-01-225-8923



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-225-8923 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.125 inches Flow Control Device: Disk Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 23.000 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Inlet/outlet Operating Pressure Differential:** Between 60.0 pounds per square inch and 150.0 pounds per square inch **Maximum Operating Pressure:** 130.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device Media For Which Designed: Oil, hydraulic 2nd response **Style Designator:** A1 straight thru **Thread Series Designator:** Npt all ends

Shelf Life:

N/a

## NSN 4810-01-225-8923

Solenoid Valve - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A046b0