NSN 4810-01-228-3506

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-228-3506 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) all ends **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Voltage In Volts And Current Type:** 115.0 ac Material: Rubber synthetic packing **Material Specification:** Qq-a-200/3 federal specification 1st material response and qq-a-225/6 federal specification 2nd material response body Media For Which Designed: Hydraulic fluid, petroleum base single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** A7 angle **Thread Series Designator:** Unf all ends Shelf Life: N/a

--

Unit Of Measure:

NSN 4810-01-228-3506

Solenoid Valve - Page 2 of 2



em			

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.