# NSN 4810-01-228-3506

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-228-3506

#### **Thread Class:**

3b all ends

**Thread Direction:** 

Right-hand all ends

### Flow Control Device:

Disk

#### Flow Control Device Normal Operation Position:

Closed

#### Maximum Operating Temp:

160.0 degrees fahrenheit single response

#### **Connection Style:**

G4 gasket sea (boss) all ends

#### Valve Operation Method:

Solenoid

#### **Connection Type:**

Threaded internal boss all ends

#### **Mounting Position:**

Horizontal or vertical

### Maximum Operating Pressure:

3000.0 pounds per square inch single response

## Thread Size:

0.750 inches all ends

## Voltage In Volts And Current Type:

115.0 ac

#### Material:

Rubber synthetic packing

### Material Specification:

Qq-a-200/3 federal specification 1st material response and qq-a-225/6 federal specification 2nd material response body

### Media For Which Designed:

Hydraulic fluid, petroleum base single response

#### Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

# Style Designator:

A7 angle

# Thread Series Designator:

Unf all ends

# Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 4810-01-228-3506

Solenoid Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.

