NSN 4810-01-240-6092

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-240-6092

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Universal

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) all ends

Current Rating In Amps:

0.022

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Vertical

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

0.500 inches all ends

Voltage In Volts And Current Type:

480.0 ac

Center To Center Distance:

1.500 inches

Phase:

Single

Special Features:

Dual solenoid; center to center distance on opposite side of valve 1.875

Frequency In Hertz:

60.0

Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

NSN 4810-01-240-6092

Solenoid Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

