

View Online at <https://aerobasegroup.com/nsn/4810-01-241-4105>

Flow Control Device:

Plug

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

500.0 degrees fahrenheit 1st response

Valve Operation Method:

Air

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

2.500 inches

Power Drive Operating Pressure:

60.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch 1st response

Outside Diameter:

7.000 inches all ends

Face To Face Distance:

10.875 inches

Thickness:

0.687 inches all ends

Bolt Hole Diameter:

0.625 inches all ends

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

4.125 inches all ends

Special Features:

Valve equipped with standard 55r actuator

Material:

Nickel alloy flow control device

Media For Which Designed:

Water, fresh 1st response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0