## NSN 4810-01-248-7152

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-248-7152

| Flow Control Device:                         |
|--|
| Disk   |
| Bonnet Type:                                 |
| Inside spring                                |
| Bonnet Attachment Method:                    |
| Bolted                                       |
| Bolt Hole Quantity:                          |
| 8 all ends                                   |
| Valve Operation Method:                      |
| Hydraulic                                    |
| Flange Shape:                                |
| Round with holes all ends                    |
| Connection Type:                             |
| Flange all ends                              |
| Valve Size:                                  |
| 4.000 inches                                 |
| Maximum Operating Pressure:                  |
| 250.0 pounds per square inch single response |
| Outside Diameter:                            |
| 9.000 inches all ends                        |
| Face To Face Distance:                       |
| 15.625 inches                                |
| Thickness:                                   |
| 0.688 inches all ends                        |
| Bolt Hole Diameter:                          |
| 0.750 inches all ends                        |
| <b>Bolt Circle Diameter:</b>                 |
| 7.500 inches all ends                        |
| Flange Face Design:                          |
| Plain all ends                               |
| Material:                                    |
| Rubber synthetic flow control device         |
| Media For Which Designed:                    |
| Water, fresh single response                 |
| Style Designator:                            |
| Err-090                                      |
| Shelf Life:                                  |
| N/a  |
| Unit Of Measure:                             |
|  |
| Demilitarization:                            |

No

## NSN 4810-01-248-7152

Globe Valve - Page 2 of 2



Fiig:

A046b0