## NSN 4810-01-256-2326

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-256-2326

view Online at https://aerobasegroup.com/nsn/4810-01-256-2326
Thread Direction:
Right-hand all ends
Flow Control Device:
Diaphragm
Flow Control Device Normal Operation Position:
Open
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) all ends
Current Rating In Amps:
0.670
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe all ends
Mounting Position:
Horizontal
Valve Size:
0.250 inches
Inlet/outlet Operating Pressure Differential:
Between 1.0 pounds per square inch and 250.0 pounds per square inch
Maximum Operating Pressure:
425.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Voltage In Volts And Current Type:
24.0 dc
Face To Face Distance:
2.120 inches
Special Features:
O/a lg. 4.375 in.; w 4.125 in.; h2.500 in.
Media For Which Designed:
Refrigerant 12 single response
Style Designator:
Err-090
Supplementary Features:
Usedon b-1bose41a01
Thread Series Designator:
Nptf all ends
Shelf Life:
N/a

N/a

## NSN 4810-01-256-2326

Solenoid Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A046b0