

View Online at <https://aerobasegroup.com/nsn/4810-01-257-2266>

Thread Direction:

Right-hand all ends

Flow Control Device:

Diaphragm

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

225.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal

Inlet/outlet Operating Pressure Differential:

Between 1.0 pounds per square inch and 150.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

1.500 inches all ends

Voltage In Volts And Current Type:

24.0 ac

Special Features:

Po/a lg 6.000 in.; o/a h 6.125in.; o/a w 1.938 in.; incl coil assbly-waterproof classf; plunger, stnls steel; bonnet, cast bronze; screw; coil retainer; enclosing tube assbly 1; screw, body bonnet 6; screw flange 2; coil 1

Material:

Rubber butadiene-acrylonitrile class nbr flow control device and plastic polyamide flow control device

Media For Which Designed:

Air 2nd response

Style Designator:

Err-090

Supplementary Features:

Used on b-1b ose41a01

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0