

View Online at <https://aerobasegroup.com/nsn/4810-01-258-1042>

Flow Control Device:

Diaphragm

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

240.0 degrees fahrenheit single response

Connection Style:

Plain (tube) all ends

Current Rating In Amps:

0.670

Valve Operation Method:

Solenoid

Connection Type:

Unthreaded internal tube all ends

Mounting Position:

Horizontal

Inlet/outlet Operating Pressure Differential:

Between 1.0 pounds per square inch and 300.0 pounds per square inch

Maximum Operating Pressure:

500.0 pounds per square inch single response

Voltage In Volts And Current Type:

24.0 dc

Outside Diameter Tube Accommodated:

0.250 inches all ends

Special Features:

O/ah4.375 in.; o/alg4.906in.; o/aw4.375 in.; solder connections; port dia.0.563 in.; bonnet 1; screw, body bonnet 4; repair kit

Material:

Plastic polytetrafluoroethylene flow control device and glass fiber flow control device

Media For Which Designed:

Refrigerant 12 1st response

Style Designator:

Err-090

Supplementary Features:

Used on b-1b ose41ao1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0