

View Online at <https://aerobasegroup.com/nsn/4810-01-263-3491>

Thread Direction:

Right-hand all ends

Flow Control Device:

Diaphragm

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Hydraulic

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Power Drive Operating Pressure:

5.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

1.000 inches all ends

Extra Long Reference Number:

1 in 100-01 globe 250 class petroleum steel screwed

Material:

Steel uns j03002 body

Material Specification:

Stnls stl 303 mfr ref single material response seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Reference Number Differentiating Characteristics:

As differentiated by extra long reference number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0