

View Online at <https://aerobasegroup.com/nsn/4810-01-268-5998>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Vertical

Valve Size:

4.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

9.000 inches all ends

Thickness:

0.688 inches all ends

First Connection Face To Centerline Distance:

5.500 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

5.500 inches

Bolt Circle Diameter:

7.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Material Specification:

Qq-n-281 cl a federal specification single material response stem

Style Designator:

Angle flanged ends

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 30263, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0