NSN 4810-01-270-6419

Solenoid Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-01-270-6419

| View Online at https://aerobasegroup.com/nsn/4810- |
|---|
| Flow Control Device: |
| Diaphragm |
| Flow Control Device Normal Operation Position: |
| Closed |
| Connection Style: |
| Socket (tube) all ends |
| Current Rating In Amps: |
| 0.160 |
| Valve Operation Method: |
| Solenoid |
| Connection Type: |
| Unthreaded internal tube all ends |
| Mounting Position: |
| Horizontal or vertical |
| Maximum Operating Pressure: |
| 500.0 pounds per square inch single response |
| Voltage In Volts And Current Type: |
| 120.0 ac |
| Outside Diameter Tube Accommodated: |
| 1.375 inches all ends |
| Phase: |
| Single |
| Special Features: |
| With manual stem |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Plastic polytetrafluoroethylene flow control device |
| Media For Which Designed: |
| Water-oil-gas single response |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| |