NSN 4810-01-272-6672

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-272-6672

Offset Distance:
5.125 inches
Flow Control Device:
Disk
Flow Control Device Normal Operation Position:
Open
Bolt Hole Quantity:
6 all ends
Current Rating In Amps:
48.000
Valve Operation Method:
Solenoid
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
2.000 inches
Inlet/outlet Operating Pressure Differential:
75.0 pounds per square inch
Voltage In Volts And Current Type:
115.0 ac
Outside Diameter:
4.625 inches all ends
Face To Face Distance:
8.000 inches
Thickness:
0.406 inches all ends
First Connection Face To Centerline Distance:
4.000 inches
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
3.500 inches all ends
Flange Face Design:
Plain all ends
Phase:
Single
Frequency In Hertz:

60.0

NSN 4810-01-272-6672

Solenoid Valve - Page 2 of 2



Copper alloy body
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Shelf Life:

Material:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A046b0