NSN 4810-01-273-1292

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-273-1292

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) all ends

Current Rating In Amps:

0.050 and 0.050

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

125.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Voltage In Volts And Current Type:

110.0 ac and 120.0 ac

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Material:

Plastic polytetrafluoroethylene seat or rubber butadiene-acrylonitrile class nbr seat

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4810-01-273-1292

Solenoid Valve - Page 2 of 2

Fiig: A046b0

