## NSN 4810-01-273-3646

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-273-3646 **Thread Direction:** Right-hand all ends Flow Control Device: Disk Flow Control Device Normal Operation Position: Universal **Maximum Operating Temp:** 140.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.075 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Inlet/outlet Operating Pressure Differential:** 30.0 pounds per square inch **Maximum Operating Pressure:** 175.0 pounds per square inch single response **Thread Size:** 0.125 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single **Special Features:** With 1 mounting bracket Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090 **Thread Series Designator:** 

Npt all ends

Shelf Life:

N/a

## NSN 4810-01-273-3646

Solenoid Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0