NSN 4810-01-282-2482

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-282-2482

Flow Control Device:
Disk
Flow Control Device Normal Operation Position:
Universal
Bolt Hole Quantity:
4 all ends
Current Rating In Amps:
0.450
Valve Operation Method:
Solenoid
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Vertical
Valve Size:
2.000 inches
Voltage In Volts And Current Type:
120.0 ac
Outside Diameter:
6.000 inches all ends
Face To Face Distance:
6.250 inches
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
4.875 inches
Bolt Hole Diameter:
0.750 inches all ends
Bolt Circle Diameter:
4.750 inches all ends
Flange Face Design:
Plain all ends
Phase:
Single
Frequency In Hertz:
60.0
Material:
Copper alloy 922 body
Style Designator:

Err-090

NSN 4810-01-282-2482

Solenoid Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0