## NSN 4810-01-284-6071

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-284-6071 **Thread Direction:** Right-hand all ends **Flow Control Device:** Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 1.800 and 0.070 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.500 inches all ends **Voltage In Volts And Current Type:** 24.0 ac and 480.0 ac and 6.0 dc and 240.0 dc Phase: Single Frequency In Hertz: 50.0 and 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device or plastic polytetrafluoroethylene flow control device Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends **Furnished Items And Quantity:** 1 mounting bracket Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4810-01-284-6071

Solenoid Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0