## NSN 4810-01-285-6164

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-285-6164

## Thread Direction:

Right-hand all ends

## **Flow Control Device:**

Disk

## Flow Control Device Normal Operation Position:

Closed

## Maximum Operating Temp:

180.0 degrees fahrenheit single response

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

## Current Rating In Amps:

0.027

Valve Operation Method:

Solenoid

#### Connection Type:

Threaded internal pipe all ends

**Mounting Position:** 

Horizontal or vertical

## Maximum Operating Pressure:

250.0 pounds per square inch single response

## Thread Size:

0.750 inches all ends

#### Voltage In Volts And Current Type:

440.0 ac

Phase:

Single

## Frequency In Hertz:

60.0

#### Material:

Rubber butadiene-acrylonitrile class nbr flow control device

## Media For Which Designed:

Air 1st response

#### Style Designator:

Err-090

## **Thread Series Designator:**

Npt all ends

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 4810-01-285-6164

Solenoid Valve - Page 2 of 2

**Fiig:** A046b0

