

View Online at <https://aerobasegroup.com/nsn/4810-01-300-3376>

Thread Direction:

Right-hand all ends

Flow Control Device:

Stem

Flow Control Device Normal Operation Position:

Open

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) all ends

Current Rating In Amps:

0.800

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

130.0 pounds per square inch single response

Thread Size:

0.125 inches all ends

Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

Special Features:

This is an altered item from automatic switch company part no8262a262, tasker part no. 712705-99 by drill ling two holes into the underside of the valve .190-32 unf-2bx.31 deep min

Frequency In Hertz:

60.0

Material:

Rubber butadiene-acrylonitrile class nbr seat

Media For Which Designed:

Gas, inert 2nd response

Style Designator:

Err-090

Supplementary Features:

Applicable on an/msq-t43

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0