NSN 4810-01-300-3376



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-300-3376 **Thread Direction:** Right-hand all ends Flow Control Device: Stem Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.800 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 130.0 pounds per square inch single response **Thread Size:** 0.125 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single **Special Features:** This is an altered item from automatic switch company part no8262a262, tasker part no. 712705-99 by dril ling two holes into the underside of the valve .190-32 unf-2bx.31 deep min Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr seat Media For Which Designed: Gas, inert 2nd response **Style Designator:** Err-090 **Supplementary Features:**

Shelf Life: N/a

Npt all ends

Applicable on an/msq-t43

Thread Series Designator:

NSN 4810-01-300-3376

Solenoid Valve - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0