## NSN 4810-01-301-4407

Solenoid Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4810-01-301-4407

0.500 inches all ends			
Aperture Diameter:			
0.250 inches			
Flow Control Device:			
Disk			
Flow Control Device Normal Operation Position:			
Closed			
Maximum Operating Temp:			
85.0 degrees fahrenheit single response			
Connection Style:			
Err-090 all ends			
Current Rating In Amps:			
2.000			
Valve Operation Method:			
Solenoid			
Connection Type:			
Butt weld pipe all ends			
Mounting Position:			
Vertical			
Maximum Operating Pressure:			
1500.0 pounds per square inch single response			
Criticality Code Justification:			
Zzzy			
Voltage In Volts And Current Type:			
120.0 ac			
Frequency In Hertz:			
60.0			
Material:			
Nickel alloy flow control device			
Material Specification:			
Qq-n-281 federal specification single material response stem			
Media For Which Designed:			
Water, salt single response			
Style Designator:			
Err-090			
Furnished Items And Quantity:			
2 reducer and 1 lever and 1 chain			
Reference Number Differentiating Characteristics:			
Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items			
Shelf Life:			
N/a			

## NSN 4810-01-301-4407

Solenoid Valve - Page 2 of 2



 :4	$\sim$	Measure:
 nit	l IT	MESCITE.

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

Mil-std (military Standard):

Mil-c-15726 spec.