NSN 4810-01-310-4644



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-310-4644 Flow Control Device: Disk Flow Control Device Normal Operation Position: Open **Bolt Hole Quantity:** 6 all ends **Current Rating In Amps:** 17.900 **Valve Operation Method:** Solenoid or manual Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Vertical Valve Size: 1.500 inches **Maximum Operating Pressure:** 60.0 pounds per square inch single response **Voltage In Volts And Current Type:** 115.0 ac **Outside Diameter:** 5.062 inches all ends **Face To Face Distance:** 9.000 inches Thickness: 0.438 inches all ends **First Connection Face To Centerline Distance:** 6.125 inches **Bolt Hole Diameter:** 0.562 inches all ends **Bolt Circle Diameter:** 3.938 inches all ends Flange Face Design:

Plain all ends

Phase:

Single

Frequency In Hertz:

60.0

Material:

Rubber isobutylene-isoprene class iir flow control device

NSN 4810-01-310-4644 Solenoid Valve - Page 2 of 2



Media For Which Designed:
Air 2nd response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0