NSN 4810-01-317-6782

Butterfly Valve - Page 1 of 1

A046b0



| View Online at https://aerobasegroup.com/nsn/4810-01-317-6782 |
|---|
| Maximum Operating Temp: |
| 440.0 degrees fahrenheit single response |
| End Application: |
| C-17 acft |
| Current Rating In Amps: |
| 1.000 |
| Valve Operation Method: |
| Solenoid or manual |
| Maximum Operating Pressure: |
| 48.0 pounds per square inch single response |
| Voltage In Volts And Current Type: |
| 16.0 dc and 30.0 dc |
| Special Features: |
| Ylg 11.70 in. Max, w 6.80 in., depth 7.80 in. Max. Valve can be wrenched (unlocked) and can be locked at the open position. Switch |
| operation: continuity shall exist between pins "1" and "2" when valve is not fully open, continuity shall exist between pins "3" and "4" when |
| valve is not fully closed. Ambient altitude range minus 1800 feet to 50000 feet. Proof pressure 96 psig at 440 degrees f. Burst pressure 192 |
| psig at 440 degrees f. Ambient temperature minus 77 degrees f to plus 220degrees f |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia· |