NSN 4810-01-319-4959

Solenoid Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-01-319-4959

O.500 inches all ends Flow Control Device: Disk Flow Control Device Normal Operation Position: Universal Connection Style: Socket all ends Current Rating In Amps: 0.088 Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090 Shelf Life:
Flow Control Device Normal Operation Position: Universal Connection Style: Socket all ends Current Rating In Amps: 0.088 Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Flow Control Device Normal Operation Position: Universal Connection Style: Socket all ends Current Rating In Amps: 0.088 Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Connection Style: Socket all ends Current Rating In Amps: 0.088 Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Connection Style: Socket all ends Current Rating In Amps: 0.088 Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Socket all ends Current Rating In Amps: 0.088 Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Current Rating In Amps: 0.088 Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Valve Operation Method: Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Solenoid Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Connection Type: Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Unthreaded internal pipe all ends Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Mounting Position: Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Horizontal or vertical Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Voltage In Volts And Current Type: 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Material: Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Plastic polytetrafluoroethylene flow control device Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Media For Which Designed: Refrigerant 12 single response Style Designator: Err-090
Refrigerant 12 single response Style Designator: Err-090
Style Designator: Err-090
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: