

View Online at <https://aerobasegroup.com/nsn/4810-01-324-3259>

**Bonnet Attachment Method:**

Bolted or union

**Maximum Operating Temp:**

220.0 degrees fahrenheit single response

**Minimum Operating Temp:**

-32.0 degrees fahrenheit

**End Application:**

U/o a/m32c-19; nha 83-84107

**Valve Operation Method:**

Solenoid

**Flange Shape:**

Round all ends

**Connection Type:**

Flange all ends

**Valve Size:**

4.841 inches

**Maximum Operating Pressure:**

50.0 pounds per square inch single response

**Opening Pressure Setting:**

7.0 pounds per square inch

**Outside Diameter:**

5.000 inches all ends

**Face To Face Distance:**

6.320 inches

**Thickness:**

0.076 inches all ends

**Flange Face Design:**

Raised with curve and radius all ends

**Raised Face Height:**

0.015 inches all ends

**Raised Face Diameter:**

5.000 inches all ends

**Butterfly Valve Size:**

4.841 inches

**Special Features:**

Manufacturers suggested name is valve, throttle, primary air

**Material:**

Aluminum body

**Media For Which Designed:**

Air single response

**Style Designator:**

Err-090

**Furnished Items And Quantity:**

2 reducer and 2 adapter

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0