

View Online at <https://aerobasegroup.com/nsn/4810-01-324-3259>

Bonnet Attachment Method:

Bolted or union

Maximum Operating Temp:

220.0 degrees fahrenheit single response

Minimum Operating Temp:

-32.0 degrees fahrenheit

End Application:

U/o a/m32c-19; nha 83-84107

Valve Operation Method:

Solenoid

Flange Shape:

Round all ends

Connection Type:

Flange all ends

Valve Size:

4.841 inches

Maximum Operating Pressure:

50.0 pounds per square inch single response

Opening Pressure Setting:

7.0 pounds per square inch

Outside Diameter:

5.000 inches all ends

Face To Face Distance:

6.320 inches

Thickness:

0.076 inches all ends

Flange Face Design:

Raised with curve and radius all ends

Raised Face Height:

0.015 inches all ends

Raised Face Diameter:

5.000 inches all ends

Butterfly Valve Size:

4.841 inches

Special Features:

Manufacturers suggested name is valve, throttle, primary air

Material:

Aluminum body

Media For Which Designed:

Air single response

Style Designator:

Err-090

Furnished Items And Quantity:

2 reducer and 2 adapter

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0