

View Online at <https://aerobasegroup.com/nsn/4810-01-324-4271>

Bonnet Attachment Method:

Bolted or union

Maximum Operating Temp:

500.0 degrees fahrenheit single response

Minimum Operating Temp:

-32.0 degrees fahrenheit

End Application:

Nha p/n 83-84107; u/o a/m32c-19

Valve Operation Method:

Air or solenoid

Flange Shape:

Round all ends

Connection Type:

Flange all ends

Valve Size:

1.341 inches

Maximum Operating Pressure:

50.0 pounds per square inch single response

Opening Pressure Setting:

7.0 pounds per square inch

Outside Diameter:

1.572 inches all ends

Face To Face Distance:

5.120 inches

Thickness:

0.089 inches all ends

Raised Face Height:

0.072 inches all ends

Raised Face Diameter:

1.500 inches all ends

Butterfly Valve Size:

1.341 inches

Special Features:

Manufacturers suggested name is valve assembly, throttle, primary air; includes reduce (2) p/n 89121334, swivel adapter(2) p/n 89121332 and scram/servo valve(1) p/n 83-83534

Material:

Aluminum

Media For Which Designed:

Air single response

Style Designator:

Err-090

Furnished Items And Quantity:

2 reducer and 2 adapter

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0