

View Online at <https://aerobasegroup.com/nsn/4810-01-324-4271>

**Bonnet Attachment Method:**

Bolted or union

**Maximum Operating Temp:**

500.0 degrees fahrenheit single response

**Minimum Operating Temp:**

-32.0 degrees fahrenheit

**End Application:**

Nha p/n 83-84107; u/o a/m32c-19

**Valve Operation Method:**

Air or solenoid

**Flange Shape:**

Round all ends

**Connection Type:**

Flange all ends

**Valve Size:**

1.341 inches

**Maximum Operating Pressure:**

50.0 pounds per square inch single response

**Opening Pressure Setting:**

7.0 pounds per square inch

**Outside Diameter:**

1.572 inches all ends

**Face To Face Distance:**

5.120 inches

**Thickness:**

0.089 inches all ends

**Raised Face Height:**

0.072 inches all ends

**Raised Face Diameter:**

1.500 inches all ends

**Butterfly Valve Size:**

1.341 inches

**Special Features:**

Manufacturers suggested name is valve assembly, throttle, primary air; includes reduce (2) p/n 89121334, swivel adapter(2) p/n 89121332 and scram/servo valve(1) p/n 83-83534

**Material:**

Aluminum

**Media For Which Designed:**

Air single response

**Style Designator:**

Err-090

**Furnished Items And Quantity:**

2 reducer and 2 adapter

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0