## NSN 4810-01-328-6272

Solenoid Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-01-328-6272

Maximum Operating Temp: 85.0 degrees celsius single response  Current Rating In Amps: 0.500  Valve Operation Method: Solenoid  Maximum Operating Pressure: 700.0 pounds per square inch single response  Voltage In Volts And Current Type: 110.0 ac  Frequency In Hertz: 60.0  Material: Stainless steel body  Reference Number Differentiating Characteristics: Quality control in accordance with navships 0948-045-7010 material identification and control instruction for subsafe items
Current Rating In Amps: 0.500  Valve Operation Method: Solenoid  Maximum Operating Pressure: 700.0 pounds per square inch single response  Voltage In Volts And Current Type: 110.0 ac  Frequency In Hertz: 60.0  Material: Stainless steel body  Reference Number Differentiating Characteristics:
Valve Operation Method: Solenoid Maximum Operating Pressure: 700.0 pounds per square inch single response Voltage In Volts And Current Type: 110.0 ac Frequency In Hertz: 60.0 Material: Stainless steel body Reference Number Differentiating Characteristics:
Valve Operation Method: Solenoid  Maximum Operating Pressure: 700.0 pounds per square inch single response  Voltage In Volts And Current Type: 110.0 ac  Frequency In Hertz: 60.0  Material: Stainless steel body  Reference Number Differentiating Characteristics:
Maximum Operating Pressure: 700.0 pounds per square inch single response Voltage In Volts And Current Type: 110.0 ac Frequency In Hertz: 60.0 Material: Stainless steel body Reference Number Differentiating Characteristics:
Maximum Operating Pressure: 700.0 pounds per square inch single response Voltage In Volts And Current Type: 110.0 ac Frequency In Hertz: 60.0 Material: Stainless steel body Reference Number Differentiating Characteristics:
700.0 pounds per square inch single response  Voltage In Volts And Current Type:  110.0 ac  Frequency In Hertz:  60.0  Material:  Stainless steel body  Reference Number Differentiating Characteristics:
Voltage In Volts And Current Type:  110.0 ac  Frequency In Hertz:  60.0  Material:  Stainless steel body  Reference Number Differentiating Characteristics:
110.0 ac Frequency In Hertz: 60.0 Material: Stainless steel body Reference Number Differentiating Characteristics:
Frequency In Hertz: 60.0  Material: Stainless steel body  Reference Number Differentiating Characteristics:
Material: Stainless steel body Reference Number Differentiating Characteristics:
Material: Stainless steel body Reference Number Differentiating Characteristics:
Stainless steel body Reference Number Differentiating Characteristics:
Reference Number Differentiating Characteristics:
Quality control in accordance with navships 0948-045-7010 material identification and control instruction for subsafe items
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A046b0