NSN 4810-01-335-7223



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-335-7223 Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Bolt Hole Quantity:** 4 all ends **End Application:** Horn air operated p/n 2-4 fig 144-2-ch onboard 180 ft c.G. Vessels **Current Rating In Amps:** 5.000 **Valve Operation Method:** Manual or solenoid Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Vertical Valve Size: 1.000 inches **Maximum Operating Pressure:** 300.0 pounds per square inch single response **Voltage In Volts And Current Type:** 115.0 ac **Outside Diameter:** 4.250 inches all ends **Face To Face Distance:** 7.000 inches Thickness: 0.437 inches all ends **Bolt Hole Diameter:** 0.531 inches all ends **Bolt Circle Diameter:**

3.125 inches all ends
Flange Face Design:
Plain all ends
Phase:
Single
Frequency In Hertz:
60.0
Material:
Stainless steel stem

NSN 4810-01-335-7223

Solenoid Valve - Page 2 of 2



Media For Which Designed:
Air single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0