NSN 4810-01-339-9639

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-339-9639

Thread Class:
2a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Spool
Flow Control Device Normal Operation Position:
Universal
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Manifold assembly
Connection Style:
G60b plain (pipe) all ends
Current Rating In Amps:
1.500
Valve Operation Method:
Solenoid
Connection Type:
Threaded cartridge all ends
Mounting Position:
Vertical
Thready Qty Per Inch (tpi):
12 all ends
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
1.437 inches all ends
Voltage In Volts And Current Type:
24.0 dc
Material:
Stainless steel body and aluminum body
Material Specification:
Qq-s-763 federal specification single material response body and qq-a-225 federal specification single material response body
Media For Which Designed:
Hydraulic fluid, petroleum base single response
Style Designator:
Err-090
Thread Series Designator:
Un all ends
Shelf Life:
N/a

NSN 4810-01-339-9639

Solenoid Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0