## NSN 4810-01-345-3826

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-345-3826 **Thread Direction:** Right-hand all ends Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **End Application:** 1730-00-274-9130 **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.120 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.500 inches all ends **Voltage In Volts And Current Type:** 115.0 ac Phase: Single Frequency In Hertz: 50.0 and 60.0 Material: Aluminum bodyrubber polymethylene-perfluoroalkylene class fkm packing Media For Which Designed: Air single response **Style Designator:** Err-090 **Thread Series Designator:** Nptf all ends Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 4810-01-345-3826

Solenoid Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0