NSN 4810-01-353-0407

Flow Control Device Normal Operation Position:

Solenoid Valve - Page 1 of 2

Flow Control Device:

Bolt Hole Quantity:

Disk

Open

4 all ends



View Online at https://aerobasegroup.com/nsn/4810-01-353-0407

| Current Rating In Amps: |
|------------------------------------|
| 0.100 |
| Valve Operation Method: |
| Solenoid |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal or vertical |
| Valve Size: |
| 2.000 inches |
| Voltage In Volts And Current Type: |
| 440.0 ac |
| Outside Diameter: |
| 6.000 inches all ends |
| Face To Face Distance: |
| 7.500 inches |
| Thickness: |
| 0.625 inches all ends |
| Bolt Hole Diameter: |
| 0.750 inches all ends |
| Bolt Circle Diameter: |
| 4.750 inches all ends |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.062 inches all ends |
| Raised Face Diameter: |
| 3.625 inches all ends |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Steel comp 304 body |
| |

NSN 4810-01-353-0407

Solenoid Valve - Page 2 of 2



| Media For Which Designed: |
|---------------------------|
| Oil single response |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A046b0