## NSN 4810-01-367-1847

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-367-1847

view online at https://aclobacogroup.com/non/ 1010 of 001 1011
Thread Class:
2a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Flow Control Device Normal Operation Position:
Universal
Maximum Operating Temp:
320.0 degrees fahrenheit single response
Connection Style:
Err-090 all ends
Valve Operation Method:
Solenoid
Connection Type:
Threaded cartridge all ends
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
16 all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
1.625 inches all ends
Voltage In Volts And Current Type:
24.0 dc
Material:
Steel seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Thread Series Designator:
Un all ends
Specification Data:
07988-spc-100-n-00-24-la professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

No

## NSN 4810-01-367-1847

Solenoid Valve - Page 2 of 2

**Fiig:** A046b0

