## NSN 4810-01-367-4782

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-367-4782

## Thread Direction:

Right-hand all ends

## Flow Control Device:

Disk

## Flow Control Device Normal Operation Position:

Closed

## Maximum Operating Temp:

180.0 degrees fahrenheit single response

## **Connection Style:**

G9 plain, optional en (pipe) all ends

## Current Rating In Amps:

0.084

Valve Operation Method:

Solenoid

#### Connection Type:

Threaded internal pipe all ends

**Mounting Position:** 

Horizontal or vertical

#### Maximum Operating Pressure:

150.0 pounds per square inch single response

#### Thread Size:

0.750 inches all ends

#### Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

#### Frequency In Hertz:

60.0

#### Material:

Copper alloy bodyrubber butadiene-acrylonitrile class nbr flow control device

#### Media For Which Designed:

Water-oil-gas single response

#### Style Designator:

Err-090

#### **Thread Series Designator:**

Npt all ends

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 4810-01-367-4782

Solenoid Valve - Page 2 of 2

**Fiig:** A046b0

