## NSN 4810-01-369-3917

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-369-3917

Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 100.0 degrees fahrenheit single response **Current Rating In Amps:** 4.700 **Valve Operation Method:** Solenoid Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Horizontal Valve Size: 2.000 inches **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Voltage In Volts And Current Type:** 120.0 ac **Outside Diameter:** 6.000 inches all ends **Face To Face Distance:** 7.375 inches Thickness: 0.500 inches all ends **Bolt Hole Diameter:** 0.750 inches all ends **Bolt Circle Diameter:** 4.750 inches all ends Flange Face Design: Plain all ends Phase: Single Frequency In Hertz: 60.0

Material:

Copper alloy bodynickel alloy flow control devicenickel alloy stem

## NSN 4810-01-369-3917

Solenoid Valve - Page 2 of 2

Fiig: A046b0



Material Specification:
Astmb61 assn standard single material response body
Media For Which Designed:
Water, fresh 1st responsewater, salt 2nd response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No