NSN 4810-01-371-4374



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-371-4374 **Thread Direction:** Right-hand all ends **Flow Control Device:** Disk Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.260 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Thread Size:** 0.375 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Copper alloy bodyrubber butadiene-acrylonitrile class nbr flow control device or plastic polytetrafluoroethylene flow control devicerubber butadiene-acrylonitrile class nbr seat Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 4810-01-371-4374

Solenoid Valve - Page 2 of 2



Fiig:

A046b0