## NSN 4810-01-416-6883



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-416-6883 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Offset Distance: 0.625 inches Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Minimum Operating Temp:** -65.0 degrees fahrenheit **End Application:** Howell dehydrator model 6750 mk 1 for the 170 ft. Patrol coastal (pc-1) class ships **Connection Style:** G4 gasket sea (boss) all ends **Current Rating In Amps:** 0.400 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss all ends **Mounting Position:** Vertical **Maximum Operating Pressure:** 6000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Voltage In Volts And Current Type:** 115.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Steel comp 303 body Media For Which Designed: Nitrogen, gaseous 2nd response **Style Designator:** 

Err-090

**Thread Series Designator:** 

Unf all ends

## NSN 4810-01-416-6883

Solenoid Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0