

View Online at <https://aerobasegroup.com/nsn/4810-01-419-3660>

Offset Distance:

10.500 inches

Flow Control Device:

Piston

Flow Control Device Normal Operation Position:

Universal

Bolt Hole Quantity:

6 all ends

End Application:

Supply class aoe

Current Rating In Amps:

1.900

Valve Operation Method:

Solenoid

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal

Valve Size:

2.000 inches

Inlet/outlet Operating Pressure Differential:

75.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Voltage In Volts And Current Type:

120.0 ac

Outside Diameter:

5.562 inches all ends

Face To Face Distance:

7.000 inches

Thickness:

0.438 inches all ends

First Connection Face To Centerline Distance:

3.750 inches

Bolt Hole Diameter:

0.562 inches all ends

Bolt Circle Diameter:

4.438 inches all ends

Flange Face Design:

Plain all ends

Phase:

Single

Special Features:

3 way valve

Frequency In Hertz:

60.0

Material:

Nickel alloy stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0