

View Online at <https://aerobasegroup.com/nsn/4810-01-422-2863>

**Flow Control Device Normal Operation Position:**

Closed

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

100.0 degrees fahrenheit single response

**End Application:**

Strategic sealift conversion ships class

**Current Rating In Amps:**

0.100

**Valve Operation Method:**

Solenoid

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Mounting Position:**

Horizontal or vertical

**Valve Size:**

1.500 inches

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

120.0 ac

**Outside Diameter:**

5.000 inches all ends

**Face To Face Distance:**

6.125 inches

**Thickness:**

0.688 inches all ends

**Bolt Hole Diameter:**

0.625 inches all ends

**Bolt Circle Diameter:**

3.875 inches all ends

**Flange Face Design:**

Raised straight all ends

**Raised Face Height:**

0.062 inches all ends

**Raised Face Diameter:**

2.875 inches all ends

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Material:**

Stainless steel body

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Style Designator:**

Err-090

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0