

View Online at <https://aerobasegroup.com/nsn/4810-01-422-2863>

Flow Control Device Normal Operation Position:

Closed

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

100.0 degrees fahrenheit single response

End Application:

Strategic sealift conversion ships class

Current Rating In Amps:

0.100

Valve Operation Method:

Solenoid

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Valve Size:

1.500 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Voltage In Volts And Current Type:

120.0 ac

Outside Diameter:

5.000 inches all ends

Face To Face Distance:

6.125 inches

Thickness:

0.688 inches all ends

Bolt Hole Diameter:

0.625 inches all ends

Bolt Circle Diameter:

3.875 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

2.875 inches all ends

Phase:

Single

Frequency In Hertz:

60.0

Material:

Stainless steel body

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0