NSN 4810-01-430-7345

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-430-7345 **Thread Direction:** Right-hand all ends Flow Control Device: Disk Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **End Application:** Engine, aircraft, f1 **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.260 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 125.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr seat Media For Which Designed: Air 1st response **Style Designator:** Err-090 **Thread Series Designator:** Nptf all ends

Furnished Items And Quantity:
1 cap
Shelf Life:

N/a

NSN 4810-01-430-7345

Solenoid Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0